

	concrete work	20mm nominal size for reinforced concrete work for walls exceeding 20cm thickness (straight and curved) beams, girders, stairs, columns, (square or rectangular) battens and lintels etc. excluding steel reinforcement but including centering and shuttering, laid in position, completed in all respects.						
4.	Brick work	First class brick work laid in cement sand mortar 1:4 in foundation and plinth			CUM.	12		
5.	Cement plaster	12mm thick cement plaster 1:4			CUM.	40.5		
6.	Refilling of earth	Refilling of excavated earth in layers of 15 cm			CUM.	90		
7.	Filling	Filing of sand in sand pit			CUM.	42		
8.	Steel structure	Structure steel work in compound girders or stanchions built up from two or more R.S. joists or channel section or plates, angle etc. welded including cutting and fixing all lattice bars, stiffeners, gusset plates, bolts, butts welding, rods etc. completed with flange plates, heads, sole plates, angle connections etc. with hoisting and erecting in position with two or more channels or plates or angle irons etc.			Kg.	12200		
9.	MS Bolts and anchor	Supplying of MS bolts round holding down of Anchor bolts with nuts and washer plates complete			Kg.	82		
10.	TMT Steel Bars	FE 500 EQR TMT steel bars for R.C.C. works, where not included in the complete ratio of R.C.C. including bending, binding and placing in position complete			Kg.	1750		
11.	Roof work	High tensile fabric roof/canopy in the area			SQM.	35		

